

1700V, 25A SILICON CARBIDE SiC SCHOTTKY DIODE

FEATURES

- ▲ High Surge Current Capability SiC Schottky
- ▲ Maximum Operating Junction Temperature over 175°C
- ▲ Zero Reverse and Forward Recovery
- ▲ Fast and Temperature-independent Switching
- ▲ Positive Temperature Coefficient on V_F

ADVANTAGES AND BENEFITS

- ▲ Extremely Low Standby and Switching Power Losses
- ▲ Higher Efficiency than when using Si Diodes
- ▲ High Frequency Operation
- ▲ Very Low Heat Sink Requirements
- ▲ Paralleling of Devices Without Thermal Runaway

DESCRIPTION

KE17DJ25 is a family of high performance 1700V, 25A Silicon Carbide (SiC) Schottky with enhanced surge current capabilities, bale to operate at high frequencies and temperatures in excess 175°C.

SiC Schottky diodes offer zero reverse and forward recovery, making them ideal for high frequency and high efficiency applications, with minimum heat sinking requirements.



APPLICATIONS

- ▲ Rectification, Voltage Blocking, Boost and Free Wheeling
- ▲ EV Chargers
- ▲ Switching Mode Power Supplies (SMPS)
- ▲ Power Factor Correction (PFC)
- ▲ Uninterruptible Power Supplies (UPS)
- ▲ Wind Turbine and Solar Inverters
- ▲ Motor Drives
- ▲ High Voltage Multipliers
- ▲ Induction Heating
- ▲ Snubbers

KEY PERFORMANCE

Parameter	Value
V_{RRM}	1700V
$I_F @ T_C=135^\circ\text{C}$	25A
Q_C	150nC

PACKAGING



QUICK ORDERING INFORMATION

Part Number	Package	Marking
KE17DJ25B	Bare die	
KE17DJ25T47	TO-247-2L	KE17DJ25

Other packages and packaging configurations available and also possible upon request.

ABSOLUTE MAXIMUM RATINGS

Unless otherwise stated, specification applies for $T_C=25^\circ\text{C}$.

Parameter	Symbol	Values	Unit	Note/Test Condition
DC Blocking Voltage	V_R	1700	V	
Repetitive Peak Reverse Voltage	V_{RRM}	1700	V	$T_J=25^\circ\text{C}$
Surge Peak Reverse Voltage	V_{RSM}	1700	V	
Continuous Forward Current	I_F	25	A	$T_C=142^\circ\text{C}$, $R_{\theta JC}<0.4^\circ\text{C/W}$
Repetitive Peak Forward Surge Current	I_{FRM}	95	A	$T_C=25^\circ\text{C}$, $t_p=10\text{ms}$ half sinewave
Non-repetitive Peak Forward Surge Current	I_{FSM}	120	A	$T_C=25^\circ\text{C}$, $t_p=10\text{ms}$ half sinewave
Power Dissipation	P_{tot}	370	W	$T_C=25^\circ\text{C}$
Operating Temperature Range	T_J	-55 to +175	$^\circ\text{C}$	
Storage Temperature Range	T_{STG}	-55 to +175	$^\circ\text{C}$	

ELECTRICAL CHARACTERISTICS

Unless otherwise stated, specification applies for $-55^{\circ}\text{C} < T_J < 175^{\circ}\text{C}$.

Parameter	Symbol	Values			Unit	Note/Test Condition	
		Min	Typ	Max			
Forward Voltage	V_F		1.6 2.8	1.8 3.3	V	$T_J=25^{\circ}\text{C}$ $T_J=175^{\circ}\text{C}$	$I_F=25\text{A}$
Reverse Current	I_R		3 15	50 300	μA	$T_J=25^{\circ}\text{C}$ $T_J=175^{\circ}\text{C}$	$V_R=1700\text{V}$
Total Capacitive Charge	Q_C		155 255		nC	$V_R=800\text{V}$ $V_R=1700\text{V}$	$I_F=25\text{A}$ $di/dt=200\text{A}/\mu\text{s}$ $T_J=25^{\circ}\text{C}$
Total Capacitance	C		2050 127 108		pF	$V_R=0.1\text{V}$ $V_R=500\text{V}$ $V_R=1000\text{V}$	$f=1\text{MHz}$, $T_J=25^{\circ}\text{C}$

THERMAL CHARACTERISTICS

Parameter	Symbol	Values		Unit	Note/Test Condition
		Typ	Max		
Junction-case Thermal Resistance	R_{TH-JC}	0.4	0.6	$^{\circ}\text{C}/\text{W}$	

TYPICAL PERFORMANCE




Fig 1. Typical Forward I-V characteristics over Temperature.




Fig 2. Typical Reverse I-V characteristics over Temperature.




Fig 3. Diode Capacitance C(pF) versus reverse voltage.




Fig 4. Typical capacitive charge (nC) versus reverse voltage.

DETAILED ORDERING INFORMATION

K ↓ Source K = CALY Technologies	E ↓ Temperature range: E = -55°C to +175°C	17 ↓ Rated Voltage: 17 = 1700V	DJ ↓ Device / Type DJ = Diode / JBS (MPS)	25 ↓ Rated Current: 25 = 25A	T47 ↓ Package: T47 = TO-247-2L
--	--	--	---	--	--

Part Number	Temperature Range	Package	Pin Count	Marking
KE17DJ25B	-55°C to +175°C	Bare die		
KE17DJ25T47	-55°C to +175°C	TO-247-2L	2	KE17DJ25

Other packages, packaging configurations and finishing materials possible upon request. MOQ may apply.

PACKAGE OUTLINE
TO247-2

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.83	5.21	0.190	0.205
A1	2.29	2.54	0.090	0.100
A2	1.91	2.16	0.075	0.085
b	1.07	1.32	0.042	0.052
b1	1.88	2.13	0.074	0.084
c	0.51	0.66	0.020	0.026
D	20.80	20.90	0.819	0.823
D1	16.56	17.83	0.652	0.702
D2	0.51	1.35	0.020	0.053
E	15.49	16.26	0.610	0.640
e	5.44 BSC		0.214 BSC	
E1	13.46	14.02	0.530	0.552
E2	4.27	4.52	0.168	0.178
E3	1.40	1.65	0.055	0.065
L	19.30	19.81	0.760	0.780
L1	4.14	4.39	0.163	0.173
Φ P	3.51	3.56	0.138	0.140
Φ P1	7.06	7.32	0.278	0.288
Q	5.46	5.64	0.215	0.225
S	6.15 BSC		0.242 BSC	

M3 Screw: 1nm (8.8lbf-in)

Unique Lot Assembly Code

YY	Last two digits of assembly year (e.g. 19 = 2019).
WW	Assembly week (01 to 52).
M	Assembly location code.
NN	Assembly lot code (01 to 99).

REVISION HISTORY

Revision	Date	Description
1A	2019-08-12	First issue
2A	2019-11-06	Updated values, package and added curves.

IMPORTANT NOTICE & DISCLAIMER

Information in this document supersedes and replaces all information previously supplied. Information in this document is provided solely in connection with CALY Technologies products.

The information contained herein is believed to be reliable. CALY Technologies makes no warranties regarding the information contained herein. CALY Technologies assumes no responsibility or liability whatsoever for any of the information contained herein. CALY Technologies assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. CALY Technologies reserves the right to make changes, corrections, modifications or improvements to this document and the information herein without notice. Customers should obtain and verify the latest relevant information before placing orders for CALY Technologies products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

Unless expressly approved in writing by an authorized representative of CALY Technologies, CALY Technologies products are not designed, authorized or warranted for use in military, aircraft, space, life-saving, or life-sustaining applications, nor in products or systems where failure or malfunction may result in personal injury, death, or property or environmental damage.

General Sales Terms & Conditions apply.

CONTACT US

For more information on CALY Technologies' products, technical support or ordering:

Website: caly-technologies.com

Email: sales@caly-technologies.com
info@caly-technologies.com

CALY Technologies SAS

CS52132

56 Bd Niels Bohr, Bat CEI2

69603 Villeurbanne Cedex

France